# HEURISTIC FORMULATIONS

GALA NO-101, COSMOS INDUSTRIAL ESTATE, NEXT TO BASCO, NAIKPADA, WALIV, VASAI-EAST, DIST-PALGHAR-401208, MAHARASHTRA, TEL NO- +91-9820216401/ +91-9320202171

## Technical Data Sheet

# Aar Coat

## Products

Aar Coats (Bases 1 to 14)

## DESCRIPTION

Aar coats are differently formulated extenders base, combined with lime-based binders, which can be tinted to give a wide range of colours. This can then be applied to make many textures and effects as desired.

## APPLICATION PROPERTIES

| | |
|---|---|
| 1) Volatile Organic Compound: | No VOC |
| 2) Color: | Base colour (Can be tinted for desired shades) |
| 3) Finish: | Matte |
| 4) Weight Solids: | 100% |

## USE PROPERTIES

| | |
|---|---|
| 1) Shelf Life: | 3 months from date of manufacture (if unopened) store indoors |
| 2) Flash Point (SETA): | Not Applicable |
| 3) Thinner | Water (do not use organic solvents) |
| 4) Clean Up: | Water and mild soap |
| 5) Application Equipment: | Brush, Trowel, and airless or conventional spray |
| 6) Application Temperature: | 20°- 38° C for surface, paint and ambient air |
| 7) Application Humidity: | Maximum of 85% relative humidity |
| 8) Storage: | Store in a cool dry place |

AARKA PAINTS आरका पेन्ट्स
JUGNU Glow Paint जुगनू ग्लो पेन्ट्
STENCIL PAINTS स्टेन्सील पेन्ट्

## TECHNICAL DATA SHEET

## RECOMMENDED USAGE

As designer texture, decorative interior and exterior walls

## SURFACE PREPARATION

Surface must be clean, dry and in sound condition, free from loose mill scales, dirt, dust, rust, oil and grease. Remove all loose scales, peeling, flaking paint, rust, corrosion and chalk from the surface before painting. Ensure the health of the wall for internal humidity and leakages.

## RECOMMENDED COVERAGE PER COAT (DRY FILM)

| | |
|---|---|
| Coverage | $ft^2$/lit |
| Smooth surface: | 5 ± **8** sq.ft. (Depending on surface and design) |
| Rough surface: | 2 ± **5** sq.ft.(Depending on the surface) |

### Recommended to apply two coats for better protection

Note: Trowel or roller application may require multiple coats to achieve maximum film thickness.

## RECOAT SCHEDULE

**Temperature:** (25 ± 5ºC)

**Application between**

| | |
|---|---|
| 1) Touch Time: | 3-5 hours |
| 2) Recoat Time: | 9 to 10 hours |
| 3) Dry Hard Time: | 22-24 hours |

## SAFETY

This product passes for environmentally friendly criteria

Use personal protective tools and equipment's while applying for personal safety

## OTHER INFORMATION

**HEALTH AND SAFETY INFORMATION:**
In case of allergies to the using this product discontinue immediately and wash with clean water and seek your physician's help immediately

Aarka Paints is the trade brand name for M/s. Heuristic Formulations. The information provided here is to the best of our knowledge and is provided in good faith, immune to any responsibility or liability arising out of its use/misuse.

AARKA PAINTS आरका पेन्ट्स JUGNU Glow Paint जुगनू ग्लो पेन्ट् STENCIL PAINTS स्टेन्सील पेन्ट्