HEURISTIC FORMULATIONS

GALA NO-101, COSMOS INDUSTRIAL ESTATE, NEXT TO BASCO, NAIKPADA, WALIV, VASAI-EAST, DIST-PALGHAR-401208, MAHARASHTRA, TEL NO- +91-9820216401/ +91-9320202171

Technical Data Sheet

Cimento

Products

Cimento (Bases WS, MD, BD)

DESCRIPTION

Cimento is acrylic base polished, crushed natural extender paste, which can be tinted to give a wide range of colours. Application with different tools gives antique to venetian finishes.

APPLICATION PROPERTIES

1) Volatile Organic Compound:	Under Permissible level
2) Color:	Base colour (Can be tinted for desired shades)
3) Finish:	Matte
4) Weight Solids:	65% ± 5%

USE PROPERTIES

1) Shelf Life:	1 years from date of manufacture (if unopened) store indoors
2) Flash Point (SETA):	Not Applicable
3) Thinner	Water (do not use organic solvents)
4) Clean Up:	Water and mild soap
5) Application Equipment:	Brush, Trowel, and airless or conventional spray
6) Application Temperature:	20°- 38° C for surface, paint and ambient air
7) Application Humidity:	Maximum of 85% relative humidity
8) Storage:	Store in a cool dry place

AARKA PAINTS आरका पेन्ट्स
JUGNU Glow Paint जुगनू ग्लो पेन्ट
STENCIL PAINTS स्टेन्सील पेन्ट

TECHNICAL DATA SHEET

RECOMMENDED USAGE

As designer texture, decorative interior and exterior walls

SURFACE PREPARATION

Surface must be clean, dry and in sound condition, free from loose mill scales, dirt, dust, rust, oil and grease. Remove all loose scales, peeling, flaking paint, rust, corrosion and chalk from the surface before painting. Ensure the health of the wall for internal humidity and leakages.

RECOMMENDED COVERAGE PER COAT (DRY FILM)

Coverage	ft^2/lit
Smooth surface:	5 ± **8** sq.ft. (Two coats depending on surface and design)

Recommended to apply two coats for better protection

Note: Brush, Trowel or roller application may require multiple coats to achieve maximum film thickness.

RECOAT SCHEDULE

Temperature:	**Application between** (25 ± 5ºC)
1) Touch Time:	3-5 hours
2) Recoat Time:	9-10 hours
3) Dry Hard Time:	24-36 hours

SAFETY

This product passes for environmentally friendly criteria

Use personal protective tools and equipment's while applying for personal safety

OTHER INFORMATION

HEALTH AND SAFETY INFORMATION:
In case of allergies to the using this product discontinue immediately and wash with clean water and seek your physician's help immediately

Aarka Paints is the trade brand name for M/s. Heuristic Formulations. The information provided here is to the best of our knowledge and is provided in good faith, immune to any responsibility or liability arising out of its use/misuse.

AARKA PAINTS आरका पेन्ट्स JUGNU Glow Paint जुगनू ग्लो पेन्ट् STENCIL PAINTS स्टेन्सील पेन्ट्