HEURISTIC FORMULATIONS

GALA NO-101, COSMOS INDUSTRIAL ESTATE, NEXT TO BASCO, NAIKPADA, WALIV, VASAI-EAST, DIST-PALGHAR-401208, MAHARASHTRA, TEL NO- +91-9820216401/ +91-9320202171

Technical Data Sheet

Marmarino

Products

Marmarino

DESCRIPTION

Aarka Clear coat is the top protective coat for architectural and decorative applications. This product utilizes a combination of modified-acrylic emulsion that provides protection against weathering, and environmental elements. It may be used on both exterior and interior surfaces, dries quickly, and is for areas subject to exterior weather conditions.

Aarka Clear Coat is available in Gloss and Matte finishes. This top coat seals the expensive decorative wall finishes and thus protects for longer life.

APPLICATION PROPERTIES

1) Volatile Organic Compound:	Permissible level
2) Color:	Base colour (Can be tinted for desired shades)
3) Finish:	Matte
4) Weight Solids:	40% ± 2%

USE PROPERTIES

1) Shelf Life:	2 years from date of manufacture (if unopened) store indoors
2) Flash Point (SETA):	> 212°F (100° C)
3) Thinner	Water (do not use organic solvents)
4) Clean Up:	Water and mild soap
5) Application Equipment:	Brush, roller, and airless or conventional spray
6) Application Temperature:	10°- 43° C for surface, paint and ambient air
7) Application Humidity:	Maximum of 85% relative humidity
8) Storage:	Store in a cool dry place

AARKA PAINTS आरका पेन्ट्स JUGNU™ Glow Paint जुगनू ग्लो पेन्ट् STENCIL PAINTS® स्टेन्सील पेन्ट्

TECHNICAL DATA SHEET

RECOMMENDED USAGE

As a top protective coat for designer, texture, decorative interior and exterior walls

SURFACE PREPARATION

Surface must be clean, dry and in sound condition, free from loose mill scales, dirt, dust, rust, oil and grease. Remove all loose scales, peeling, flaking paint, rust, corrosion and chalk from the surface before painting. Ensure the health of the wall for internal humidity and leakages.

RECOMMENDED COVERAGE PER COAT (DRY FILM)

Coverage	ft^2/lit
Smooth surface:	80 ± 120 sq.ft.
Rough surface:	45 ± 60 sq.ft.

Recommended to apply two coats for better protection

Note: Brush or roller application may require multiple coats to achieve maximum film thickness.

RECOAT SCHEDULE

Temperature:	**Application between** (25 ± 5ºC)
1) Touch Time:	2 hour
2) Recoat Time:	5 hours
3) Dry Hard Time:	10 Days

SAFETY

This product passes for environmental friendly criteria

Use personal protective tools and equipment's while applying for personal safety

OTHER INFORMATION

HEALTH AND SAFETY INFORMATION:
In case of allergies to the using this product discontinue immediately and wash with clean water and seek your physician's help immediately

Aarka Paints is the trade brand name for M/s. Heuristic Formulations. The information provided here is to the best of our knowledge and is provided in good faith, immune to any responsibility or liability arising out of its use/misuse.

AARKA PAINTS आरका पेन्ट्स JUGNU Glow Paint जुगनू ग्लो पेन्ट् STENCIL PAINTS स्टेन्सील पेन्ट्