HEURISTIC FORMULATIONS

GALA NO-101, COSMOS INDUSTRIAL ESTATE, NEXT TO BASCO, NAIKPADA, WALIV, VASAI-EAST, DIST-PALGHAR-401208, MAHARASHTRA, TEL NO- +91-9820216401/ +91-9320202171 / +91-8080608607.

Technical Data Sheet

AARKA STENCIL PAINTS

DESCRIPTION

Aarka stencil paint is specially formulated to give fast drying definitive shape when applied while stenciling. To be used for interior surfaces. Inherently is matte in finish unless specified.

Aarka stencil paints are tint able with strainers and available for dark shades, light shades, in yellow base and in red base in matte finishes. Also, available for tint able dark shade and light shade glossy finishes.

APPLICATION PROPERTIES

1) Volatile Organic Compound:	Permissible level
2) Color:	As specified
3) Finish:	Gloss/Matte as specified
4) Weight Solids:	45% ± 15%

USE PROPERTIES

1) Shelf Life:	2 years from date of manufacture (if unopened) store indoors
2) Flash Point (SETA):	> 212°F (100° C)
3) Thinner	Water (do not use organic solvents)
4) Clean Up:	Water and mild soap
5) Application Equipment:	Brush and roller
6) Application Temperature:	10°- 43° C for surface, paint, and ambient air
7) Application Humidity:	Maximum of 85% relative humidity
8) Storage:	Store in a cool dry place

AARKA PAINTS आरका पेन्ट्स ™ JUGNU Glow Paint जुगनू ग्लो पेन्ट् ™ STENCIL PAINTS स्टेन्सील पेन्ट् ®

TECHNICAL DATA SHEET

RECOMMENDED USAGE

As decorative stenciling for interior surfaces.

SURFACE PREPARATION

Surface must be clean, dry, flat and in sound condition, free from loose mill scales, dirt, dust, rust, oil and grease. Remove all loose scales, peeling, flaking paint, rust, corrosion and chalk from the surface before painting. Ensure the health of the wall for internal humidity and leakages.

RECOMMENDED COVERAGE PER COAT (DRY FILM)

Coverage	Depends on type of stencils

Recommended to apply two coats for better results

Note: Brush or roller application may require multiple coats to achieve opaque film.

RECOAT SCHEDULE

Temperature:	**Application between** (25 ± 5ºC)
1) Touch Time:	10 mins
2) Recoat Time:	20 mins

SAFETY

This product passes for environmental friendly criteria

Use personal protective tools and equipment's while applying for personal safety

OTHER INFORMATION

HEALTH AND SAFETY INFORMATION:
In case of allergies to the using this product discontinue immediately and wash with clean water and seek your physician's help immediately

Aarka Paints is the trade brand name for M/s. Heuristic Formulations. The information provided here is to the best of our knowledge and is provided in good faith, immune to any responsibility or liability arising out of its use/misuse.

AARKA PAINTS आरका पेन्ट्स JUGNU Glow Paint जुगनू ग्लो पेन्ट् STENCIL PAINTS स्टेन्सील पेन्ट्